



Technical Data Sheet

FLEXOGRIP™ CR DCR600SW

DESCRIPTION

- Industrial protective glove gauge 10
- Ambidextrous shape doubles glove life.
- Latex knit wrist ensures snug fit.
- 5 sizes available: 7, 8, 9, 10 and 11.
- Single glove packaging.

CHARACTERISTICS

- Seamless non-stop process, knitted with technical fibers including Tsunooga™ UHMWPE synthetic fibers 1 DPF (Dine Per Filament) and stainless steel threads offering excellent cut resistance with a nice, soft texture.
- 21CFR (USA) and European Directives compliant for food contact. List of food contact, which include medium fatty meat, is available by request
- **Glass-free**

PERFORMANCES

- Provides the highest level of cut resistance for EN388
- Highest dexterity for a gauge 10
- Flexible and comfortable.
- Special materials make it ideal for food processing.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical hazards)

APPLICATIONS

- Ideal for use in meat preparation environments, abattoirs and butchers (nitrile under-glove suggested)

WASHING INSTRUCTION

- Do not bleach
- Max washing temperature 90°C
- Do not iron
- Washed gloves, being used, do not perform the same as a new glove, cut resistance may be affected, certification no longer valid

LIMITATIONS

- Do not use for handling liquids.
- Do not use with rotating machines in which glove may get caught.



(Glove won't be printed. Textile-tag applied)

This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to Personal Protective Equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN420

5 Dexterity

EN388

3 Abrasion

5 Cut

4 Tear

3 Puncture



3543

EN 388:2003
Mechanical hazard

V = sizes available

style	5 XXS	6 XS	7 S	8 L	9 M	10 XL	11 XXL	12 XXXL
Flexogrip CR DCR600SW			✓	✓	✓	✓	✓	