



Technical Data Sheet

FLEXOGRIP™ CR MAX DCR6136

DESCRIPTION

- Industrial protective glove.
- Synthetic textile liner with a synthetic coating PU based
- Elasticated knit wrist for snug fit.
- 5 sizes available: 7, 8, 9, 10 and 11.
- Trade unit 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Seamless knitted technology with technical fibers including Tsunooga™ UHMWPE synthetic fibers 1 DPF (Dine Per Filament) and Spandex®. **Knitted process patented**
- Stretchable and comfortable to decrease fatigue
- Palm Fit black polyurethane coated
- Elasticated knit wrist with elastic bead to ensure best snug-fit.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical hazards)

PERFORMANCES

- Optimized comfort and dexterity for a highly durable glove with top performances. **The patented knitted process allows the hand palm to freshness feeling while in operation**
- Highest level of cut protection (level 5 EN388).
- Top abrasion resistance.

APPLICATIONS

- For handling needing a very good protection against cuts.
- Mechanical industries, handling of sharp components, automotive industry, glass industry.
- Metal waste recovery centers

LIMITATIONS

- Not suitable to work in highly oily work station and to manipulate liquids.
- Do not use to manipulate pointed objects
- Do not use with rotating machines such as drills, lathes, etc, in which glove may get caught.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to Personal Protective Equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN 388:2003
Mechanical hazard

4543

EN420

5 Dexterity

EN388

4 Abrasion

5 Cut

4 Tear

3 Puncture

√ = sizes available

style	5 XXS	6 XS	7 S	8 L	9 M	10 XL	11 XXL	12 XXXL
Flexogrip CR MAX DCR6136			√	√	√	√	√	