



Technical Data Sheet

NITRAFLEX™ DH8230 U3

DESCRIPTION

- Industrial protective glove.
- Supported glove with elastic knit wrist to ensure snug fit
- 5 sizes available: 6, 7, 8, 9 and 10.
- Trade unit: 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Lightweight dark grey coating made of nitrile foam, palm fit.
- Seamless polyamide liner, gauge 15, available in blue to enhance visibility or color coding
- **Unique textile pattern enhancing performance in grip, granting excellent wearability, stress reducing for long time usage**
- Fine and stretchable stitches for excellent comfort.
- Elasticated knit wrist with elastic bead to ensure best snug-fit.
- DMF-free.
- In conformity with the standards EN420 (General requirements) and EN388 (Mechanical Hazards) by CE notified laboratory.

PERFORMANCES

- High degree of flexibility and durability with optimum dexterity.
- Excellent comfort.
- Excellent abrasion resistance.
- Excellent grip in low-medium oily environment

APPLICATIONS

- Ideal for use in general assembly, engineering applications, screwing and bolting. All ambient requiring color reference or good visibility for safety purpose
- Building industry

LIMITATIONS

- Do not use for full liquid immersion and pointed objects.
- Avoid use with rotating machines in which glove may get caught



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to Personal Protective Equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN420

5 Dexterity



3131

EN388

3 Abrasion

1 Cut

3 Tear

1 Puncture

EN 388 : 2003

Mechanical hazard

V = sizes available

style	5 XXS	6 XS	7 S	8 L	9 M	10 XL	11 XXL	12 XXXL
Nitriflex DH8230 U3		✓	✓	✓	✓	✓		