



Technical Data Sheet

FLEXOGRIP™ LITE DH3135

DESCRIPTION

- Industrial protective glove.
- Black PU synthetic coating on a blue nylon liner.
- 5 available sizes: 6, 7, 8, 9 and 10
- Single pair packed, trade unit 12 pairs, 240 pairs in a transit case.

CHARACTERISTICS

- Polyamide (Nylon) textile liner made with a seamless non-stop process.
- **Gauge 18, very lightweight ergonomic design, fine and stretchable.**
- Flat dipped polyurethane palm fit coating, **silicone free**
- Elastic knit wrist to ensure snug fit.
- In compliance with the standards EN420 (General Requirements) and EN388 (Mechanical Hazards) by the notified body CTC.

PERFORMANCES

- Excellent adaptability thanks to its extensibility.
- Superior comfort and dexterity (level 5 out of 5).
- Textile back ensures the best hand breathability thanks to its fineness.
- Good abrasion resistance.

APPLICATIONS

- For general mechanical handlings where comfort is required in dry condition
- Ideal for use in automotive industry, painting, print shops, general maintenance, small parts handling, logistic platform, supermarkets handlings (no food compliance)

LIMITATIONS

- Do not use for handling liquids and pointed objects.
- Do not use with a rotating machine in which glove may get caught.
- Limited protection at the wrist.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to Personal Protective Equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN420

5 Dexterity



EN 388 : 2003
Mechanical hazard

EN388

3 Abrasion
1 Cut
1 Tear
0 Puncture

√ = sizes available

style	5 XXS	6 XS	7 S	8 L	9 M	10 XL	11 XXL	12 XXXL
Flexogrip Lite DH3135		√	√	√	√	√		