



## Technical Data Sheet

### NITRAFLEX™ DH8130

#### DESCRIPTION

- Industrial protective glove.
- Supported glove with elastic knit wrist to ensure snug fit
- 5 sizes available: 6, 7, 8, 9 and 10.
- Trade unit: 12 pairs, 144 pairs in a transit case.

#### CHARACTERISTICS

- Lightweight grey coating made from nitrile smooth .
- Palm fit coating.
- Seamless polyamide liner, gauge 13.
- Fine and stretchable stitches for excellent comfort.
- Elasticated knit wrist with elastic bead to ensure best snug-fit.
- DMF-free.
- In conformity with the standards EN420(General requirements) and EN388 (Mechanical Hazards) by CE notified laboratory.



#### PERFORMANCES

- High degree of flexibility and durability with optimum dexterity.
- Excellent comfort.
- Excellent abrasion resistance.
- Excellent grip in medium-low oily environment

#### APPLICATIONS

- Ideal for use in general assembly, engineering applications, screwing and bolting.
- Building industry
- Photography laboratory
- quality control , Logistic

#### LIMITATIONS

- Do not use for full liquid immersion and pointed objects.
- Avoid use of rotating machines in which glove may get caught

This glove is certified to comply with the essential safety requirements of the regulation (EU)2016/425 relative to Personal Protective Equipment submitted to CE type examination issue by a notified laboratory which certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during the tests



EN420

5 Dexterity

EN388

3 Abrasion

1 Cut

2 Tear

1 Puncture

X EN/ISO13997(1999)



3121X

EN388 :2016  
Mechanical hazard

V = sizes available

style	5 XXS	6 XS	7 S	8 L	9 M	10 XL	11 XXL	12 XXXL
Nitraflex DH 8130			✓	✓	✓	✓		